

PART 6: SECTION 5.5

ROLLER SHUTTERS

Notes:

- 1) The manual override option is only approved on internally face fixed units with internally face fixed motor boxes.
- 2) This assumes installation direct to substrate and not via intermediate substrates, such as plasterboard.

Shellcast Systems Limited

Unit 2, Frederick Road, Hoo Farm Industrial Estate, Kidderminster DY11 7RA UK

Tel: +44 (0)1562 750 700 • Fax: +44(0)1562 750 800

E-mail: technical@shellcast-shutters.co.uk • Website: www.shellcast-shutters.co.uk

Certificate No: 707a to LPS 1175: Issue 5

Security Shutters

Product Name	Model	Type	Clear Opening Dimensions Minimum Size (m) Height	Clear Opening Dimensions Minimum Size (m) Width	Clear Opening Dimensions Maximum Size (m) Height	Clear Opening Dimensions Maximum Size (m) Width	Security Rating	LPCB Ref. No.
Linframe	CD38.1	Built-in rolling shutter	0	0.4	6	5	1	707a/01
	CD38.2	Built-in rolling shutter	0	0.4	6	5	2	707a/02
	CD38.3	Built-in rolling shutter	0	0.4	6	5	3 ⁽²⁾	707a/03
	CD38/P.1	Built-in rolling shutter	0	0.4	6	3	1	707a/04
	CD38/S.1	Built-in rolling shutter	0	0.4	6	3	1	707a/05
	CD60.1	Built-in rolling shutter	0	0.4	6	5	1	707a/06
	CD60.2	Built-in rolling shutter	0	0.4	6	5	2	707a/07

Notes:

- 1) The approval applies to the shutters when installed strictly in accordance with the instructions provided with the product
- 2) To achieve this grade the lockable override cover plate must be fitted and locked, and the key removed to a secure location.